

PROJECT DESCRIPTION

I. GENERAL

This project involves the modification of an existing Traffic Control Signal with interconnect at the intersection of MD 235 and Pegg Road in St. Mary's County. The modification is due to the construction of a Dash-in store driveway accessing MD 235 approximately 150' south of Pegg Road. MD 235 is assumed to run in a north-south direction.

- II. INTERSECTION OPERATION
 - 1. There will be no change to the intersection operation.
 - 2. The existing base-mounted cabinet shall be maintained at this intersection.

III. SPECIAL NOTE

All field wiring to the existing controller cabinet shall be terminated to the appropriate controller cabinet connectors by the Contractor and labeled. All other controller cabinet wiring will be performed by the S.H.A. Signal Shop. Contact Mr. Ed Rodenhizer at (410) 787-7650 seventy—two hours in advance of intended work. The SHA shop is to disconnect the telemetry cable and reconnect after rerouting.


EQUIPMENT LISTS


A. EQUIPMENT TO BE FURNISHED AND/OR INSTALLED BY THE CONTRACTOR.

QUANTITY		SPEC. SECTION	DESCRIPTION
	LS	106	Mobilization
	LS	106	Maintenance of traffic.
100	SF	104	Temporary traffic sign.
2	UD	105	Flashing arrow panels.
80	LF	815	Furnish and install sawcut.
10	LF	805	Furnish and install 1" liquid tight flexible non-metallic electrical conduit (detector wire sleeve).
185	LF	805	Furnish and install 2" polyvinyl chloride electrical conduit (Schedule 80) (trenched).
1	EA	811	Furnish and install handhole (frame and cover).
300	LF	810	Furnish and install loop wire (No. 14 A.W.G.) encased in $^{1}/_{4}^{\prime\prime}$ flexible tubing.
455	LF	810	Furnish and install 2-conductor electrical cable (No. 14 A.W.G.) (aluminum shielded).
200	LF		Pull back and reroute existing interconnect cable.
1	EA	822	Remove handhole.

CONSTRUCTION DETAILS

- A. Install 6' x 6' loop detector encased in $\frac{1}{4}$ " flexible tubing (4-turns).
- B. Install handhole.
- C. Install 1" liquid tight flexible non-metallic electrical conduit (detector wire sleeve).
- D. Pullback existing interconnect cable from cabinet and reroute thru proposed conduit as shown. Existing riser is to be maintained. (See Wiring Diagram).
- E. Install 2" polyvinyl chloride electrical conduit (Schedule 80) (trenched). (Note: Use exisiting elbow and riser on utility pole.)
- F. Install 2" polyvinyl chloride electrical conduit (Schedule 80) (trenched) prior to installation of proposed geometrics.
- G. Install 2" polyvinyl chloride electrical conduit (Schedule 80) (trenched).
- H. Use existing handhole. (Cap and abandon attached conduit that is to be replaced).
- J. Use exisiting conduit.
- K. Use existing handhole.
- L. Use existing cabinet.
- M. Remove handhole (Cap and abandon attached conduits).





	(
STREET TRAFFIC STUDIES, LTD.	
Gateway International 1302 Concourse Drive, Suite 104 Linthicum, Maryland 21090 Ph (410) 859-3553 Fax (410) 859-3579	F

3260A.DGN

REVISIONS	APPROVALS	
	4,/	
	ASST. CHIEF TEDD SECTION	
© 7/18/97 REPLACE SAMPLING LOOPS, CONDUIT SHA NO.: BW 998 MB2		
RRZ MAR BRIL THE	ASST. DISTRICT ENGINEER, TRAFFIC	
B 10/10/93 REVISE SIGNAL EQUIPMENT TO AVOID CONFLICT WITH BURIED CABLE. REVISED SIGNAL PHASING		DF
RG/DCI	CHEF, TRAFFIC ENGINEERING DESIGN DIVISION	CH
A 7/28/93 REPLACE PROPOSED STRAIN POLES WITH MAST ARM POLES	5	DA

DIRECTOR, TRAFFIC & SAFETY

MARYLAND DOT - STATE HIGHWAY ADMINISTRATION
Office of Traffic & Safety
TRAFFIC ENGINEERING DESIGN DIVISION

MD 235 AND PEGG RD / NORTH GATE RD

 DRAWN BY:
 J.E.H.
 COUNTY:
 ST. MARY'S
 TS NO.
 3287C
 SHEET NO.

 CHECK BY:
 3-93
 F.A.P. NO.
 N-AD-25 (3)
 T.I.M.S. NO.
 1 OF 1

 SCALE:
 1" = 20"
 S.H.A. NO.
 SM-766-501-571
 T.I.M.S. NO.
 1 OF 1

UTILITY	LEGEND_
——— G ———— G ————	GAS MAIN
w w	WATER MAIN
——— \$ ———— \$ ———	SEWER MAIN
	FLECTOIC CADLEC

W WATER MAIN
SEWER MAIN
E E E E ELECTRIC CABLES
A A A A A A ERIAL CABLES
T T T T T TELEPHONE CABLES